




uPVC OVERLAY PANELS



www.royaldoors.co.uk

uPVC OVERLAY PANELS

The pinnacle of design, functionality, thermal insulation, and acoustic insulation.

$U_p = \text{up to } 0,5$
 W/m^2K

Height: 1500 - 2270* mm
Width: 500 - 990 mm
Thickness: 36 - 70 mm

*2280 for lacquered panels

The panel consists of a GFK surface plate, a core (thermally insulated sandwich with reinforcement), and an HPL plate on the inside.





Finishes

- Decorative pilasters (grooving) in any RAL K5 Classic colour on the exterior side of the door
 - Stainless steel applications, black or silver, fully integrated into the panel (depending on the model)
 - Handles mounted in the body of the infill or recessed
-

Panel cladding or painting in RAL K5 Classic colours *

- Independent finishing for the interior and exterior sides
 - The possibility of using two different colours on selected panels
-

Glazing

- Availability of glazing configurations depends on the selected panel
- Up to triple-glazed units
- A wide selection of decorative and solar control glass
- Easy replacement of damaged glass

*The catalogue of veneers is constantly updated.

uPVC OVERLAY PANELS

☆ High-quality workmanship

🏠 Sandwich-type core with hard foam insulation and reinforcements

📄 GFK - single-sided overlay

🎨 Wide range of decorative films



1



2



3



4



5



6



7



8



9



10



11



12



13



14



15



16



17



18



19



20



21



22



23



24



25



26



27



28



29



30



31



32



33



34



35



36



37



38

This publication does not constitute a commercial offer. It is not a basis for complaints. The presented photos are illustrative images and not actual photos of the products.

